

Applicant respectfully submits claims 1-8 for consideration by the Examiner. No new matter has been added, all amendments are supported in the specification.

Respectfully submitted,

SOFER & HAROUN L.L.P.

By: 

Robert M. Haroun  
Reg No. 34,345  
342 Madison Avenue  
Suite 1921  
New York, NY 10173  
(212) 697-2800  
Fax (212) 697-3004

Dated:

2/11/02

Attorney Docket No. 33-020con



COPY OF PAPERS  
ORIGINALLY FILED

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

-----X

In re Application of

Examiner: TBA

Billings

Group Art Unit: TBA

Serial No. 10/027,776

Filed: December 20, 2001

For: LAMP BALLAST FOR REDUCING INTERFERENCE CURRENT

-----X

**PRELIMINARY AMENDMENT**  
**REPLACEMENT PAGES**

Honorable Assistant Commissioner of Patents  
Washington, DC 20231

Dear Sirs:

These replacement pages accompany the Preliminary Amendment filed herewith,  
illustrating the amended claims without markings.

Replacement pages

CLAIMS

What is claimed is:

1. A ballast circuit for supplying AC voltage and current to a gas discharge lamp mounted in a troffer upon the application of DC voltage and current, said troffer having a ground connection, said circuit comprising:
  - a transformer including a first and a second primary winding;
  - first and second transistors, each having base, collector and emitter terminals, said base terminal of each said transistor coupled to a drive terminal of said second primary winding;
  - a constant current flow network coupled to said drive terminal so as to maintain said circuit in an oscillating mode;
  - said first primary winding configured to be coupled across said at least one lamp such that a capacitance at a first end of said lamp relative to said transformer is equal to a capacitance at a second end of said lamp relative to said transformer; and
  - a current supply source coupled to said troffer ground connection.
2. The apparatus of claim 1, wherein said capacitance at said first and second ends of said at least one lamp is provided by a capacitor.
3. The apparatus of claim 1, further comprising a DC supply voltage source coupled to said transformer for supplying a variable DC supply voltage.
4. The apparatus of claim 3, wherein said current supply source is a positive

Replacement pages

supply line of said DC supply voltage source.

5. The apparatus of claim 4, wherein said positive supply line of said DC supply voltage source is further coupled to said drive terminal via a resistor for providing start-up current.

6. The apparatus of claim 5, wherein said positive supply line of said DC supply voltage source is further coupled to a center tap terminal of said first primary windings.

7. The apparatus of claim 3, wherein said DC supply voltage source has negative and positive supply lines, said circuit further comprising:

a capacitor coupled to and disposed between said negative and positive supply lines; and

an inductor disposed in said negative supply line,

wherein said circuit is configured to reduce a current flow in one said supply line relative to said other supply line.

8. The apparatus of claim 1, wherein said constant current flow network further comprises an inductor coupled in series with a resistor and a diode coupled to said drive terminal of said second primary winding.